



Digital Signage involves the remote-controlled distribution and playback of digital content such as TV programs, advertisements, menus, and various forms of information - on networks displays. These displays can range from large digital billboards to smaller screens, either at a single location or across multiple sites. The goal is to target the audience with relevant information.

Assured Digital Signage has showcased a Digital Signage application on the Android platform. This application features the ability to update content remotely via a web browser, and supports the playback of video content, images, HTML web pages, and scrolling text messages.

Key Features:

- Android 7.1 operating system
- Rockchip RK3288 Quad-core CPU
- 2GB DDR3 + 8GB Flash
- 802.11 b/g/n internal Wifi
- 4G/WIFI/WLAN Network connection
- Remote Management Software optional
- Smart air control system for cooling and heating
- Sunlight readable and dustproof function
- IP65 waterproof function
- Light sensor

Designed for:

- POS
- Hotel
- Self-service Terminal
- Public Information Display
- Hospitality
- In-vehicles And Transportation

SVRCS - 750DDLAZ



Specifications

PANEL	Panel Model	75inch TFT LED
	Max Resolution	3840x2160
	Aspect Ratio	16:09
	Pixel Pitch	0.4296x0.4296
	Viewing Angle	89/89/89/89
	Contrast Ratio	1200 : 1
	Brightness	2500cd/m ²
	Response Time	8ms
	Display Area (mm)	1549.44x871.56mm
	Panel Size(mm)	1758x993x45mm
	Screen Weight	28.5Kg
	Lamp Type	WLED
INTERNAL MEDIA PLAYER	CPU	Quad-core ARM Cortex-A17,1.8GHz
	GPU	ARM Mali-T764
	RAM	2GB DDR3
	ROM	8GB Flash
	OS	Android 7.1
CONNECTOR	USB 2.0	X2
	HDMI (Output)	X1
	TF	X1
	Rj45	X1
	4G SIM (Optional)	X1
CONNECTIVITY	LAN	RJ45 Port, 10/100M Ethernet
	WiFi	Built-in WiFi 802.11B/G/N
	4G (Optional)	LTE
FILE SUPPORT	Video	H.264, MKV, WMV9, MPEG 1/2/4, HD Divx, Xvid, RM/RMVB;
	Image	BMP/PNG/GIF/JPEG
	Audio	MP3,WMA,WAV,EAAC+, MP2 dec, Vorbis (Ogg), AC3, FLAC, APE, BSAC
	Scrolling Text	txt
DISPLAY MODE		Portrait
TOUCH		Capacitive touch options

HDMI DISPLAY	Output Mode	HDMI 480P	HDMI 576P
		HDMI 720P 50Hz	HDMI 720P 60Hz
		HDMI 1080I 50Hz	HDMI 1080I 60Hz
		HDMI 1080P 24Hz	HDMI 1080P 50Hz
		HDMI 1080P 60Hz	
PERATURE CONTROLLER		TemCooling fan can be set to start running when the whole temperature reached 60 °C	
SPD		Lightning protection device	
LEAKAGE PROTECTION SWITCH		110~220V*1	
COOLING SYSTEM	Blowing machine Cooling fan Noise DB (A)	Air cooling system: 45 blowing machines and 15 cooling fans, stable and reliable performance <55dB	
LEVEL OF PROTECTION		IP65	
ON-SCREEN DISPLAY LANGUAGES		English, French, German, Italian, Polish, Russian, Simplified Chinese, Spanish, Turkish, Arabic, Japanese, Traditional Chinese etc.	
POWER	Mains Power	AC 100-240V, 50-60 Hz	
	Consumption	1300W	
SOUND	Built-in Speakers	2 x 10W	
DIMENSION & WEIGHT	Machine Size	2480x352x1237.5mm	
		1350X50X387mm(stand base)	
	Machine Weight	135KG / 17KG(stand base)	
	Carton Size	2570x320x1225mm	
	Carton Weight	160KG	
	Wooden case Size Wooden case Weight	2630x380x1285mm(1PCS) 188KG	
OTHER	Regulatory Approvals Warranty	CE, FCC, ROHS	
		2 years warranty	
ACCESSORIES	Included	Remote Control, Power supply, User manual, Keys, Screws	