SH35N(U) 35" SHELF EDGE DIGITAL DISPLAY





Open a Coke, open happiness



ULTRA HD DEFINITION

Ultra HD resolution 3840 x 200 ensures vivid, high-impact images and videos at the point of sale.



HIGHLY DURABLE SCREENS

Reliable commercial grade screens enable your shelf displays to run smoothly 24/7.



ULTRA NARROW BEZEL

Slim and modern design featuring LED backlight technology delivers a captivating look.



EXCEPTIONAL BRIGHTNESS

Elevated brightness 500nits provides extraordinary colour expression and greater visibility.



ADSDS TECHNOLOGY PANEL

Commercial grade ADSDS panels ensures incredible image quality and colour depth with no fall-off in colour accuracy, as well as achieving ultimate lifelike colour from an ultra-wide viewing angle



NATIVE STRETCHED LCD

Non-resizing/cutting LCD Panel, so no Broken glass, fragile sealing, microcracks, light leakage.



OPT.1: HDMI DAISY CHAIN

With HDMI Daisy Chain, Each screen can be setup as videowall position with the remote controller or OSD board equipped, easy setup. Connect an external player by HDMI and play it as video wall.



OPT.2: ANDROID PLAYER

Integrated with Android player, allows to update content via USB or online CMS. You can also install any 3rd party CMS Software if required.

Web: www.vivisign.com

Email: info@vivisign.com

SPECIFICATIONS

STESTIO!

Panel

Diagonal Size

35"

Resolution

3840 x 200

Brightness (Typ.)

500 nit

Contrast Ratio

1000:1

Viewing Angle

178 / 178 (H/V)

Colors

1.07G. 72% NTSC

LED Life

>50.000hours

AA Area (mm)

877.824(W)×45.72(H)

Power

Type External **Power Supply**

AC 100 - 240V, 50/60Hz - DC 12V

Power Type C

Type C x 1

OPT.1: LCD Monitor with HDMI Daisy Chain

AV Ports

HDMI IN x1, HDMI OUT x1

OPT.2: BUILT-IN Android PC

CPU

Quad-core Cortex A55

GPU

Mali-G31 MP2

RAM

2GB

Internal Memory

16GB

USB

Mirco-USB (OTG) x 1 USB 2.0 X1

Wi-Fi

802.11b/g/n

Bluetooth

BT4.2

OS

Android OS 9.0

Mechanical

Outline Size (mm)

891.6 x 60.4 x 23 891.6 x 60.8 x 29

Weight 1.8 kg

Bracket

x1

Operation

Operation Temp.

0 - 40°C

Humidity 10% - 80%

Web: www.vivisign.com

Email: info@vivisign.com