

SAMSUNG

OH Full Outdoor Signage

OH46B 46" | OH55A-S 55" | OH75A 75"

Stand out, outside. Night and day, rain or shine.

A sleek all-in-one display that's built for the outdoors.

Communicate clearly at all times. The Samsung OH Series outdoor solution features exceptional brightness and a slim yet rugged design. It'll get your message out 24/7, whether it's pouring rain at midnight or scorching sun at noon.



A true all-weather display

With certified IP56-rated protection, Samsung OH Series full outdoor signage is designed specifically to withstand the elements and fully perform in heat, cold, rain, snow and dust.¹



Humidity prevention

With hidden four fans in the downside of the signage, external humidity issues such as condensation are greatly reduced.



Attract attention anywhere, anytime

Samsung full outdoor signage is UL-verified for outdoor visibility, with peak brightness of up to 4,000 nits. Combined with a built-in auto brightness sensor, it'll deliver vivid content in all types of lighting, 24/7.



Bright, vivid, accurate communication

OH series signage delivers enhanced red, green and blue shades, for incredible color accuracy.



Outstanding visibility in direct sun

Samsung Magic Protection Glass features advanced anti-reflection technology, for exceptional visibility even in direct sunlight. And Samsung's circular polarizing technology means content can still be easily seen even while wearing polarized sunglasses.



Robust durability for screen safety

The Magic Protection Glass is tempered, with IK10-rated durability for advanced safety and protection against external impact and damage.² That helps protect against vandalism, and adds peace of mind.



Reliable and advanced software for effective management

The embedded MagicINFO Player S7, backed by the powerful TIZEN operating system, boosts overall performance and offers painless content management.³ Promotions and content throughout a network of signage can be easily changed. Transitions and playback are seamless, for a better experience for both customers and store managers.



Powerful, protective security

Powered by Samsung's proprietary Knox technology, the OH series employs comprehensive three-layer security protection. The secured platform helps minimize security attacks and supports application development.



3-year warranty

A 3-year warranty means extended protection and peace of mind.



samsung.com/display

OH Full Outdoor Signage

Model			OH46B	OH55A-S	OH75A
Panel	Diagonal Size	Class Measured	46"	55"	75"
	Type		45.9" / 116.8cm	54.6" / 138.7cm	74.5" / 189.2cm
	Resolution		1920 x 1080 (16:9)	120Hz E-LED BLU	60Hz D-LED Local Dim. BLU
	Brightness (Typ.)		3,500 nit (Peak 4,000 nit)	1920 x 1080 (16:9)	3840 x 2160 (16:9)
	Contrast Ratio		6000:1	3,500 nit (peak 4,000 nit)	3,500 nit (peak 4,000 nit)
	Viewing Angle (H/V)		178/178	6,000:1	1,200:1
	Color Gamut		72%	178/178	178/178
	Operation Hour		24/7	72%	24/7
Sound	Speaker Type		N/A	N/A	N/A
			N/A	N/A	N/A
Connectivity	INPUT	Video	HDMI 2.0 (2), HDBaseT	HDMI 2.0 (2), HDBaseT(LAN Common)	HDMI 2.0 (2)
		HDCP	HDCP 2.2	HDCP 2.2	HDCP 2.2
		Audio	N/A	N/A	N/A
		USB	USB 2.0 x 1	USB (1)	USB (1)
		RGB	N/A	N/A	N/A
	OUTPUT	Video	N/A	N/A	N/A
		Audio	Stereo Mini Jack	Stereo Mini Jack	Stereo Mini Jack
		USB	N/A	N/A	N/A
		External Control	RS232C(in/out), RJ45 (in/out), HDBaseT	RS232C (in/out), RJ45(in/out), HDBaseT	RS232C (in), RJ45(in)
		External Sensor	N/A	N/A	N/A
Power	Type	Internal	Internal	Internal	
	Power Supply	AC 100 – 240 V, 50/60 Hz	AC 100 – 240 V, 50/60 Hz	AC 100 – 240 V, 50/60 Hz	
Power Consumption	Max [W/h]	460	530	1,200	
	Typical [W/h]	205W	274	471	
	BTU (Max)	⌘ IEC 62087 measurement standard	⌘ IEC 62087 measurement standard	⌘ IEC 62087 measurement standard	
	Sleep mode	0.5	Less than 0.5W	Less than 0.5W	
	Off mode	N/A	N/A	N/A	
Mechanical Spec	Dimension (mm/in)	Set	1,069 x 623.6 x 85 mm / 42 x 24.5 x 3.3 in	1,260.6 x 731.4 x 85.0 mm / 49.6 x 28.7 x 3.3 in	1,774.8 x 1,053.4 x 130 mm / 69.8 x 41.4 x 5.1 in
	Weight (kg/lbs)	Set	115.4 x 71.3 x 20.0 mm / 45.5 x 28 x 3.8 in	1,358 x 845 x 230 mm / 53.4 x 33.2 x 9 in	1,932 x 1,251 x 367 mm / 76 x 49.2 x 14.4 in
	Mounting Hole	Set	36 kg / 79.3 lbs	46.1 kg / 101.6 lbs	134 kg / 295.4 lbs
	Protection Glass	Package	40.5 kg / 89.2 lbs	52.6 kg / 115.9 lbs	150 kg / 330.6 lbs
Operation	Humidity	10~100%	10~100% (Non-condensing)	10~80% (Non-condensing)	
	IP Rating	IP56	IP56	IP56	
	Key	Power-box Integrated, IP56 Outdoor,Built-in MagicInfo Player S7, SSSP 7.0	Power-box Integrated, IP56 Outdoor,Built-in MagicInfo Player S7, SSSP 7.0	Power-box Integrated, IP56 Outdoor,Built-in MagicInfo Player S7, SSSP 7.0	
	Orientation	Portrait / Landscape	Portrait / Landscape	Portrait / Landscape	
Special	Processor	Cortex A72 1.7GHz Quad-Core CPU	Cortex A72 1.7GHz Quad-Core CPU	Cortex A721.7GHz Quad-Core CPU	
	On-Chip Cache Memory	L1 Instruction Cache: 48KB L1 Data Cache: 32KB L2 Cache: 2MB	L1 Instruction Cache: 48KB L1 Data Cache: 32KB L2 Cache: 2MB	L1 Instruction Cache: 48KB L1 Data Cache: 32KB L2 Cache: 2MB	
Feature	Internal Player (Embedded H/W)	Graphics	Graphic resolution: 1920 x 1080 Output resolution: up to 3840 x 2160 (Scale up from graphic processing result) – Supports OpenGL ES	Graphic resolution: 1920 x 1080 Output resolution: 1920 x 1080 – Supports OpenGL ES	Graphic resolution: 1920 x 1080 Output resolution: up to 3840 x 2160 (Scale up from graphic processing result) – Supports OpenGL ES
		Storage (FDM)	8GB (3.88GB Occupied by O/S, 4.12GB Available)	8GB (3.88GB Occupied by O/S, 4.12GB Available)	8GB (3.88GB Occupied by O/S, 4.12GB Available)
	Video Decoder	FHD MFD : VP8, H.264, AVS+(60Hz)UHD MFD : HEVC, H.264, VP95K HEVC Decoder, SHVC(ATSC3.0)AVS2.0 HEVC / AVS2.0 1xUHD120p (DP, NR off, FRC bypass)	FHD MFD : VP8, H.264, AVS+(60Hz)UHD MFD : HEVC, H.264, VP95K HEVC Decoder, SHVC(ATSC3.0)AVS2.0 HEVC / AVS2.0 1xUHD120p (DP, NR off, FRC bypass)	FHD MFD : VP8, H.264, AVS+(60Hz)UHD MFD : HEVC, H.264, VP95K HEVC Decoder, SHVC(ATSC3.0)AVS2.0 HEVC / AVS2.0 1xUHD120p (DP, NR off, FRC bypass)	
	Multimedia	Audio Decoder – AC3 (DD), MPEG	Audio Decoder – AC3 (DD), MPEG	Audio Decoder – AC3 (DD), MPEG	
	IO Ports	USB 2.0	USB 2.0	USB 2.0	
	Operating System	Tizen 5.0 (VDLinux)	Tizen 5.0 (VDLinux)	Tizen 5.0 (VDLinux)	
	Certification	Safety	60950-1	60950-1	60950-1
		EMC	Class A	Class A	Class A
	Accessories	Environment	N/A	N/A	N/A
		Included	Quick Setup Guide, Regulatory Guide, Warranty Card, Power Cord, Remote Controller, Batteries	Quick Setup Guide, Regulatory Guide, Warranty Card, Power Cord, Remote Controller, Batteries	Quick Setup Guide, Regulatory Guide, Warranty Card, Power Cord, Remote Controller, Batteries

Connectivity

- RS232C IN / Out
- Audio Out
- USB
- RJ45 (LAN Out)
- HDBT (LAN In)
- HDMI In 1
- HDMI In 2
- DP In (UHD 60Hz)

OH46B



OH55A-S



OH75A



OH55A-S - Front



OH55A-S - Back



Learn More samsung.com/display samsung.com/business insights.samsung.com

Product Support 1-866-SAM4BIZ Follow Us [youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa) [@SamsungBizUSA](https://twitter.com/SamsungBizUSA)

SAMSUNG

©2022 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. All other brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screen images simulated. Non-metric weights and measurements are approximate. Specifications and designs are subject to change without notice. See samsung.com for detailed information. Printed in USA. OH-DSHT-AUG22T1

¹IP56 (Ingress Protection Rating): Degrees of protection provided by enclosures (IEC 60529). ²The IK European strength test rating uses a 0-10 scale (where 10 indicates the highest possible protection) to measure the degree of resistance against external impact. ³MagicINFO license must be purchased separately.