



ULTRA HD DEFINITION

Ultra HD resolution 3840x 160 ensures vivid, high-impact images and videos at the point of sale.



HIGHLY DURABLE SCREENS

Designed for continuous use in public spaces, these displays utilise commercial grade LCD panels, LED backlights and internal components. This means they can run 24/7 for over 50,000 hours.



NARROW BEZEL

A sleek, narrow bezel is especially important when placing multiple screens together. The compact design also adds to the aesthetic and reduces strain on shelf edges.



EXCEPTIONAL BRIGHTNESS

Elevated brightness 500nits provides extraordinary colour expression and greater visibility.



ANTI-GLARE LCD PANEL

With a non-glare (25% haze) panel, you can rest assured that your content will not be obstructed by lighting conditions outside of your control.



NATIVE STRETCHED LCD

Non-resizing/cutting LCD Panel, so no Broken glass, fragile sealing, micro-cracks, light leakage.



OPT.1: HDMI DAISY CHAIN

With HDMI Daisy Chain, Each screen can be setup as videowall position with the remote controller or OSD board equipped, easy setup. Connect an external player by HDMI and play it as video wall.



OPT.2: ANDROID PLAYER

Users can choose to integrated with Android player to update content via USB or CMS. You can also install any 3rd party CMS Software if required.

SPECIFICATIONS

Panel

Diagonal Size 47.1"	Resolution 3840 x 160	Brightness (Typ.) 500 nit	Contrast Ratio 1000:1
Viewing Angle 178 / 178 (H/V)	Colors 16.7M 72% NTSC	Surface Treat. Haze 25%	AA Area (mm) 1196.16 x 49.84mm

Power

Type External	Power Supply AC 100 - 240V, 50/60Hz - DC 12V	Power Consumption 25W
-------------------------	--	---------------------------------

OPT.1: LCD Monitor with HDMI Daisy Chain

AV Ports
HDMI IN x1, HDMI OUT x1

OPT.2: BUILT-IN Android PC

CPU Quad-core Cortex A55	GPU Mali-G31 MP2	RAM 2GB	Internal Memory 16GB
USB Mirco-USB (OTG) x 1 USB 2.0 x 1	Wi-Fi 802.11b/g/n	Bluetooth BT4.2	OS Android OS 9.0

Mechanical

Outline Size (mm) 1209 x 62.9 x 27.5/29	Weight 2.1 kg (net weight) 2.3 kg (with bracket)	Bracket x1
---	---	----------------------

Operation

Operation Temp. 0 - 40 °C	Humidity 10% - 80%
-------------------------------------	------------------------------